



Scissor Lift Function Check

Name: _____

Dept: _____

Date: _____

Make: _____

Serial #: _____

Notes: When performing any functional check:

1. To start the check, the scissor lift should be on a level surface, free from overhead obstructions and adequate clearance to the front, back and sides. Engine/motor should be stopped and controls set to the neutral position.
2. Move all parts and extend all sections to their highest positions.
3. If the component **does not work** as designed, immediately shut down the lift, remove the key and notify your AWP – POC.

Checklist Items	Operational		Comments
	Yes	No	
Outside Scissor Lift – Ground Control			
Emergency Stop Check	<input type="checkbox"/>	<input type="checkbox"/>	
Raising Lift	<input type="checkbox"/>	<input type="checkbox"/>	
Pothole Guard, Safety Arm and Scissor Sections Check	<input type="checkbox"/>	<input type="checkbox"/>	
Lowering Lift	<input type="checkbox"/>	<input type="checkbox"/>	
Emergency Lowering Check	<input type="checkbox"/>	<input type="checkbox"/>	
On Scissor Lift – Platform Control			
LED Display/Battery Condition	<input type="checkbox"/>	<input type="checkbox"/>	
Emergency Stop Check/Horn Check	<input type="checkbox"/>	<input type="checkbox"/>	
Functional Enable Switch Check	<input type="checkbox"/>	<input type="checkbox"/>	
Raise/Lower Platform	<input type="checkbox"/>	<input type="checkbox"/>	
Steering Check (Left/Right)	<input type="checkbox"/>	<input type="checkbox"/>	
Driving Check (Forward/Reverse)	<input type="checkbox"/>	<input type="checkbox"/>	